

Indoor Unit		MSZ-HJ25VA	MSZ-HJ35VA	MSZ-HJ50VA	MSZ-GF60VE	MSZ-GF71VE	
Outdoor Unit		MUZ-HJ25VA	MUZ-HJ35VA	MUZ-HJ50VA	MUZ-GF60VE	MUZ-GF71VE	
Refrigerant		R410A (*1)					
Power Source		230V - Single Phase - 50 Hz					
Cooling	Capacity	kW	2.5 (1.3-3.0)	3.15 (1.4-3.5)	5.0 (1.3-5.0)	6.1 (1.4-7.5)	7.1 (2.0-8.7)
	Total Input Power (Rated)	kW	0.730	1.040	2.050	1.79	2.13
	SEER		5.1	5.1	6.0	6.8	6.8
	Energy Efficiency Class		A	A	A+	A++	A++
Heating	Capacity (Rated)	kW	3.15 (0.9-3.5)	3.6 (1.1-4.1)	5.4 (1.4-6.5)	6.8 (2.0-9.3)	8.1 (2.2-9.9)
	Total Input Power (Rated)	kW	0.870	0.995	1.480	1.81	2.23
	SCOP		3.8	3.8	4.2	4.3	4.2
	Energy Efficiency Class		A	A	A+	A+	A+
Indoor Unit	Rated Input	kW	0.020	0.021	0.037	0.062	0.058
	Dimensions (H x W x D)	mm	290 x 799 x 232			325 x 1100 x 238	
Indoor Unit	Weight	kg	9			16	
	*Air Volume (Silent-Low-Mid-High-Silent)	m ³ /min	3.8-5.5-7.3-9.5	3.8-5.7-7.8-10.9	6.3-9.1-11.1-12.9	9.8-11.3-13.4-15.6-18.3	9.7-11.5-13.3-15.4-17.8
Indoor Unit	*Sound Pressure Level (Silent-Low-Mid-High-Silent)	dB(A)	22-30-37-43	22-31-38-45	28-36-40-45	29-37-41-45-49	30-37-41-45-49
	Outdoor Unit	Dimensions (H x W x D)	mm	538 x 699 x 249	550 x 800 x 285	880 x 840 x 330	
Outdoor Unit	Weight	kg	24	25	36	50	53
	*Air Volume (Low-Mid-High-Silent)	m ³ /min	31.5	31.5	36.3	49.2	50.1
Outdoor Unit	*Sound Pressure Level (Low-Mid-High-Silent)	dB(A)	50	50	50	55	55
	Operating Current (max.)	A	5.5	6.2	9.2	14	16.1
Outdoor Unit	Breaker Size	A	10	10	12	20	20
	Ext. Piping	Diameter (Liquid / Gas)	(mm)	6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35/15.88
Ext. Piping	Max. Length (Out-In)	m	20			30	
	Max. Height (Out-In)	m	12			15	
Guaranteed Operating Range (Outdoor)	Cooling (°C)		+15 ~ +46			-10 ~ +46	
	Heating (°C)		-10 ~ +24			-15 ~ +24	

(*1) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains refrigerant fluid with a GWP equal to 1975. Additional refrigerant would be charged in case the piping distance exceeds 5 meter.

Product Quality Control



COMFORT	DURABILITY	EFFICIENCY
Quiet operation	Strict performance tests	Energy saving
Optimal temperature distribution	Easy-to-clean design	Money saving
Clean, filtered air available	Replacement parts	Space saving

Product Quality Assurance



Environmental Vision 2021

Environmental Vision 2021 is the long-term environmental management vision of the Mitsubishi Electric Group. With the guideline of making positive contributions to the earth and its people through technology and action, the Company is working toward the realization of a sustainable society utilizing wide-ranging and sophisticated technologies as well as the promotion of proactive and ongoing actions by our employees. The Vision sets 2021 as its target year, coinciding with the 100th anniversary of Mitsubishi Electric's founding.

Dealer

Mr. SLIM

Mitsubishi
MElectric
Quality



